




PRODUCT DATA SHEET

**RONDO®**

# XPRESS® DRYWALL GRID CEILING SYSTEM



The Rondo Xpress® Drywall Grid Ceiling System is light-weight and simple to install.

The Main Tee and Cross Tee connection uses the same patented QRC clip technology that is known and preferred by installers.

With an ability to be used in acoustic, seismic and fire-rated applications, the Rondo Xpress® Drywall Grid Ceiling System offers design flexibility for flush plasterboard ceilings, bulkheads and boxed soffits.

## FIRE-RATED AND ACOUSTIC DESIGN/ SIMPLE INTEGRATION/ SEISMIC DESIGN

### BENEFITS

- Surface Finish: Z275 galvanised
- Low profile with 38mm wide face
- Integration with Rondo DONN® Exposed Grid Ceiling System
- Simple Integration of conventional light fixtures, air conditioning services and access panels
- Main Tee and Cross Tee clips have a secure connection and are easy to remove and relocate

### SUITABLE FOR

- Concealed ceiling systems
- Plasterboard, fibrous plaster and fibre cement linings
- Direct fix or fully suspended applications
- Seamless transition from a concealed to exposed grid ceiling
- Bulkheads and boxed soffits
- Corridors, without the use of suspension hangers
- Fire-rated applications
- Seismic requirements
- Acoustic ceiling solutions



STANDARDS & CODES	CEILINGS						WALLS			ACCESSORIES	FINISHING SECTIONS		ACCESS PANELS	FASTENERS
	DUO	DONN	KEY-LOCK	XPRESS	WALK-ABOUT	STUD & TRACK	STUD & TRACK	MAXIFRAME	QUIET STUD	TOP HATS	EXANGLE	EXANGLE RT	PANTHER	CERT-R-FIX
<b>NCC 2022</b> - Building Code of Australia Volumes 1 & 2														
<b>NZBC - B1/VM1</b> NZ Building Code Verification Method B1/VM1 Clause 2														
<b>NZBC - B2</b> Durability Rondo XPRESS® Drywall Grid System will have a minimum serviceable life of 15 years when installed in a dry, non- corrosive, interior installation.														
<b>AS/NZS 1170.0:2002</b> Part 0: General principles														
<b>AS/NZS 1170.1:2002</b> Part 1: Permanent, imposed & other actions														
<b>AS/NZS 1170.2:2021</b> Part 2: Wind actions														
<b>AS 1170.4:2007</b> Part 4: Earthquake actions in Australia														
<b>NZS 1170.5:2004</b> Part 5: Earthquake actions in New Zealand														
<b>NZS 4219:2009</b> Seismic performance of engineering systems in buildings														
<b>AS/NZS 4055:2021</b> Wind loads for housing														
<b>AS/NZS 4600:2018</b> Cold formed steel structures														
<b>AS/NZS 2785:2020</b> Suspended Ceilings - Design & installation														
<b>AS 3566.1:2002</b> Self-drilling screws for the building and construction industries - General requirements and mechanical properties														
<b>AS 5216:2021</b> Design of post-installed and cast-in fastenings in concrete	■	■	■	■	■	■	■	■	■					
<b>AS1530.4:2014</b> Fire resistance tests for elements of construction														
<b>AS/NZS 1530.3:1999</b> Simultaneous determination of ignitability, flame propagation, heat release and smoke release (Reconfirmed 2016)														
<b>AS 1191:2002</b> Acoustics - Method for laboratory measurement of airborne sound transmission insulation of building elements														
<b>AS/NZS ISO 717.1:2004</b> Acoustics - Airborne sound insulation														

STRUCTURAL DESIGN ACTIONS

STANDARDS & CODES	CEILING						WALLS			ACCESSORIES	FINISHING SECTIONS		ACCESS PANELS	FASTENERS
	DUO	DONN	KEY-LOCK	XPRESS	WALK-ABOUT	STUD & TRACK	STUD & TRACK	MAXIFRAME	QUIET STUD	TOP HATS	EXANGLE	EXANGLE RT	PANTHER	CERT-R-FIX
<b>ASTM C635/C635M-17</b> Standard Specification for Manufacture, Performance and Testing of Metal Suspension Systems for Acoustical Tile and Lay-in Panel Ceilings														
<b>AS 3623:1993</b> Domestic metal framing														
<b>AS/NZS 1657:2018</b> Fixed platforms, walkways, stairways & ladders. Design, construction & installation														
<b>AS/NZS 1397:2021</b> Continuous hot-dip metallic coated steel sheet & strip - Coatings of zinc & zinc alloyed with aluminium & magnesium	*													
<b>AS/NZS 1664.1:1997</b> Aluminium structures - Limit state design	●													
<b>AS/NZS 1866:1997</b> Aluminium & aluminium alloys - Extruded rod, bar, solid & hollow shapes	●													
<b>AS/NZS 2311:2017</b> Guide to the painting of buildings														
<b>AS/NZS 2589:2017</b> Gypsum Linings - Application & finishing														

- \* EXCLUDES ALUMINIUM
- APPLIES TO ALUMINIUM GRID ONLY
- REFER TO CERT-R-FIX MANUAL

For comprehensive design and installation guides please [click here](#) to access the **Rondo Professional Series**

## MATERIAL SAFETY DATA INFORMATION

### MATERIALS

Products manufactured by Rondo Building Services are produced from coated steel coil material which is classified as a non-hazardous material.

### PRODUCTION PROCESSES

A water-based soluble lubricant is used to assist with the roll forming process. These soluble lubricants are not considered hazardous when used as recommended by the manufacturer.

### HANDLING AND STORAGE

Products are supplied in pack and sub-pack quantities and should be handled in accordance with the recommendations contained in AS 1470 – Health and Safety at Work Principles and Practice.

Where mechanical lifting or moving equipment is required, trained, and licensed operators are to be used.

Metal products should be stored in an environmentally friendly area away from airborne contaminants such as acid and salt sprays.

### SAFETY

It is our recommendation that PPE should be worn when handling metal products (AS 2161 –Occupational Protective Gloves) and that they should be checked regularly for damage.

People with sensitive skin conditions should seek medical advice before prolonged handling of metal products: hands should be washed before eating and for personal hygiene.

Safety glasses (AS/NZS 1336) should be worn when cutting metal sections.


### SITE TRAINING

It is the responsibility of the contractor to ensure their employees are trained in onsite WHS procedures as these can vary from site to site.

### COMBUSTIBILITY

For more information on the steel used by Rondo visit [www.steel.com.au](http://www.steel.com.au) or [click here](#).





For more information on the Rondo Sustainability Advantage [click here](#)

ENVIRONMENTAL PRODUCT DECLARATION (EPD)

The Rondo EPD provides to a customer the Life Cycle Assessment (LCA) data for over 300 products and 53 product families.

source the LCA data by selecting the required part numbers that make up the system within one EPD.

The Rondo EPD was certified, and made available to Rondo customers in December 2020, [click here](#) to download.




RONDO WARRANTY

Rondo's quality products are backed by our comprehensive warranty.

With minimal exclusions, our warranty provides optimal peace of mind.

For more information on our warranty [click here](#).



CERTIFICATIONS

